## **Payanywhere Smart POS+**

## **Specifications** | PAX E700





os	PayDroid powered by Payanywhere
Processor	Quad-core Cortex-A53, 1.8GHz
Memory	2GB DDR + 16GB eMMC   1 x Micro SD card slot, supporting up to 128GB
Payment Module	Magstripe, EMV chip card and NFC contactless card reader with 4.3-inch color touchscreen
Camera	0.3 Megapixel fixed focus front camera & 2 megapixel fixed focus rear camera that reads 1D and 2D codes
Fingerprint Login	Optional
Display	12.5-inch all perspective IPS display   FHD 1920 x 1080 pixels capacitive touchscreen
Audio	2 x speakers
Physical buttons	1 x ON/OFF key   1 x printer paper button   1 x Volume +/- key
Communications	Wifi (2.4GHz + 5GHz) supports Probe and Hotspot   4G (TD-LTE/FDD-LTE) + 3G (WCDMA/CDMA2000)   Bluetooth 4.1 (supports iBeacon)   LAN (10/100M)
Card slots	1 x SIM
Peripheral ports	4 x type-A USB $ $ 1 x type-C USB $ $ 1 x RJ11 (24V), Cash Box $ $ 1 x RJ45 (LAN) $ $ 1 x RJ45 (RS232) $ $ 1 x audio jack $ $ 1 x charging port
Printer	3-inch thermal printer   print speed: 150mm/s   Paper width: 80mm   paper diameter: 80mm   automatic paper receipt cutter
Battery	3.7V/2200mAH rechargeable lithium ion battery
Adapter	Input: 100-240V AC, 50Hz/60Hz   Output: 24V DV, 1.5A
Indicators	1 x printer indicator: green (normal state) yellow (out of paper indicator) and red flashing (error state indicator)
Physical	L x W x H (in): 12.2 x 12.1 x 5.5   L x W x H (cm): 31 x 30.8 x 14   Weight (lb): 4.6   Weight (kg): 2.1
Environmental	0°C-50°C (32°F-122°F) operating temperature -20°C-70°C (-4°F-158°F) storage temperature
Certifications	PCI PTS 5.x, SRED   EMV L1 & L2   EMV contactless L1   Mastercard contactless Visa payWave   American ExpressPay   Discover D-PAS   Mastercard TQM   FCC Interac_FlashCL2   J/Speedy   PTCRB   CSEC   APCA   ABECS   UL   CE   IC

Name Email Phone Website