Payanywhere Smart Flex

Specifications | PAX E600







Software	The Payanywhere Application
Operating System	PayDroid powered by Android 7.1
Processor	Quad-core Cortex A53, 1.4 Ghz
Memory	1GB DDR + 8GB eMMc
Display	8-inch All-Perspective IPS Display, 800 x 1280 Pixels HD Display with Capacitive Touchscreen and customer facing display.
Communication	FD-LTE/TDD-LTE WCDMA/TD-SCDMA/EVDO GSM/CDMA Bluetooth 4.1 WiFi: 802.11 b/g/n, 2.4GHz, Support Hotspot
Audio	1 x speaker
Physical	L x W x H (in): 11.5 x 5.1 x 4.1 L x W x H (cm): 29.2 x 13 x 10.5 Weight (lb): 4.85 Weight (kg): 2.2
Printer	2-inch thermal printer head print speed: 80mm/s paper width: 58mm diameter: 50mm
Charging Base	Optional comms & charging base with ethernet
Host Peripheral Ports	1 x SIM Card Slot 2 x SIM Card Slot (optional) 1 x Audio Jack 1 x Micro SD Card Slot, Supports up to 128GB 1 x Micro USB
Base Peripheral Ports	1x Cash Drawer RJ11 (24V) $1x$ RS232 $1x$ USB Type A, USB HOST 2.0 Pogo contacts for host power supply and communication $1x$ DC power supply interface $1x$ LAN
Voltage	Input: 100-240V AC, 50Hz/60Hz Output: 9V DC, 2.5A
Cameras	0.3 megapixel camera for 1D & 2D code scanning 5-megapixel fixed focal front camera
Battery	7.2V, 2600mAh rechargeable lithium-ion battery
Physical Keys	1 x On/Off key 1 x Volume Up key 1 x Volume Down key
Indicator	Power indicator Smart card indicator
Certifications	PCI PTS 5.x CE FCC IC UL RoHs EMV L1 & L2 Visa PayWave MasterCard Contactless MasterCard TQM Amex ExpressPay Interac Flash L2 Discover D-PAS CSEC APCA ABECS

Name Email Phone Website