

Payanywhere Smart Terminal Mini

Specifications | PAX A60



**Advantage First
Merchant Services**



Software	The Payanywhere Application
Operating System	PayDroid based on Android 6.0
Processor	Application CPU: Quad-core Cortex-A7, 1.3GHz Security CPU: 32-bit RISC Core (ARMv7-M), 1.25DMIPS/MHz
Memory	1GB DDR + 8GB eMMC 2GB DDR + 16GB eMMC (optional) 1 x Micro SD Card Slot, Supports Up To 128 GB
Display	5-inch, IPS Color, HD, Touchscreen Display, 1280 x 720 pixels
Physical Keys	1 x ON/OFF Key 2 x Volume +/- Key
Communications	Wifi (2.4G) Supports Hotspot 4G (FDD-LTE/TDD-LTE) 3G (WCDMA) 2G (GSM/GPRS) Bluetooth (4.0)
Camera	5 Megapixel Auto Zoom with LED Flashlight Reads 1D & 2D Codes
Card Readers	Magnetic Card Reader Smart Card Reader Contactless Card Reader
Battery	3.6V/3350mAh Rechargeable Li-ion Battery
Audio	1 x speaker
Physical	L x W x H (in): 7.23 x 2.95 x 2.14 L x W x H (cm): 18.36 x 7.49 x 5.43 Weight (lb): 0.69 Weight (kg): 0.31 (including battery)
Location	Supports GPS
Card Slots	1 x SIM Card Slot + 2 x SAM Card Slot 2 x SIM Card Slots + 1 x SAM Card Slot
Peripheral Ports	1 x TypeC Charging USB 2.0, OTG 1 x 3.5mm Audio Jack 1 x 7pin POGO pin
Voltage	Input: 100-240V AC, 50Hz/60Hz Output: 5.0V DC, 1.0A
Indicators	1 x LED Power Indicator Contactless Transaction Lights: Blue/Yellow /Green/Red Power Indicator Smart Card Reader Indicator
Environmental	-10°C ~ 50°C (14°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 5% ~ 95% Relative Humidity, Non-Condensing
Certifications	PTS 5.x, SRED EMV L1 & L2 EMV Contactless L1 Discover D-PAS Mastercard Contactless Visa payWave American ExpressPay Mastercard TQM Interac_Flash_L2 J/Speedy L2 FCC RoHs IC

Name Email Phone Website